

Please type a plus sign (+) inside this box →


PTO/SB/29 (2/98)

Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

GAP 2508

2811

\$



CONTINUED PROSECUTION APPLICATION (CPA) REQUEST TRANSMITTAL

Submit an original, and a duplicate for fee processing.

(Only for Continuation or Divisional applications under 37 C.F.R. § 1.53(d))

CHECK BOX, if applicable
 DUPLICATE

RECEIVED

Address to:

MAP 2 1999
Assistant Commissioner for Patents
Box CPA
TECHNOLOGY CENTER 2800
SPECIAL PROGRAM CENTER C 20231

Attorney Docket No.	1958P1705DIV
First Named Inventor	FINK ET AL.
Examiner Name	Potter, R.
Group / Art Unit	2508
Express Mail Label No.	EL160875809US

This is a request for a continuation or divisional application under 37 C.F.R. § 1.53(d),
(continued prosecution application (CPA)) of prior application number 08/644,916,
filed on 5-24-96, entitled A MICROCONTROLLER HAVING AN N-BIT DATA BUS WIDTH
WITH LESS THAN N I/O PINS AND A METHOD THEREFOR
NOTES

FILING QUALIFICATIONS: The prior application identified above must be a nonprovisional application that is either: (1) complete as defined by 37 C.F.R. § 1.51(b), or (2) the national stage of an international application in compliance with 35 U.S.C. 371.

A Notice will be placed on a patent issuing from a CPA, except for reissues and designs, to the effect that the patent issued on a CPA and is subject to the twenty-year patent term provisions of 35 U.S.C. § 154(a)(2). Therefore, the prior application of a CPA may have been filed before, on or after June 8, 1995.

CPA NOT PERMITTED: A continuation-in-part application cannot be filed as a CPA under 37 C.F.R. § 1.53(d), but must be filed under 37 C.F.R. § 1.53(b).

EXPRESS ABANDONMENT OF PRIOR APPLICATION: The filing of this CPA is a request to expressly abandon the prior application as of the filing date of the request for a CPA. 37 C.F.R. § 1.53(b) must be used to file a continuation, divisional, or continuation-in-part of an application that is not to be abandoned.

ACCESS TO PRIOR APPLICATION: The filing of this CPA will be construed to include a waiver of confidentiality by the applicant under 35 U.S.C. 122 to the extent that any member of the public who is entitled under the provisions of 37 C.F.R. § 1.14 to access to, copies of, or information concerning, the prior application may be given similar access to, copies of, or similar information concerning, the other application or applications in the file jacket.

35 U.S.C. 120 STATEMENT: In a CPA, no reference to the prior application is needed in the first sentence of the specification and none should be submitted. If a sentence referencing the prior application is submitted, it will not be entered. A request for a CPA is the specific reference required by 35 U.S.C. 120 and to every application assigned the application number identified in such request, 37 C.F.R. § 1.78(a).

- Enter the unentered amendment previously filed on _____ under 37 C.F.R. § 1.116 in the prior nonprovisional application.
- A preliminary amendment is enclosed.
- This application is filed by fewer than all the inventors named in the prior application, 37 C.F.R. § 1.53 (d)(4).
 - DELETE** the following inventor(s) named in the prior nonprovisional application:
.....
.....
 - The inventor(s) to be deleted are set forth on a separate sheet attached hereto.
- A new power of attorney or authorization of agent (PTO/SB/81) is enclosed.
- Information Disclosure Statement (IDS) is enclosed:
 - PTO-1449
 - Copies of IDS Citations

RECEIVED

JAN 22 1999

TECHNOLOGY CENTER 2800
SPECIAL PROGRAM CENTER

10/14/2014 10:21:49 AM 00000005 0864916

01 FC-131

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. All comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box CPA, Washington, DC 20231.

Please type a plus sign (+) inside this box →

PTO/SB/29 (2/98)

Approved for use through 09/30/2000. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number


CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS	
	TOTAL CLAIMS (37 C.F.R. § 1.16(c) or (i))	10 -20* =	-0-	x \$ 22.00 =	\$ -0-	
	INDEPENDENT CLAIMS (37 C.F.R. § 1.16(b) or (i))	1 -3** =	-0-	x \$ 82.00 =	-0-	
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 C.F.R. § 1.16(d))			+ \$ 270.00 =	-0-	
				BASIC FEE (37 C.F.R. § 1.16)	\$ 790.00	
				Total of above Calculations =	790.00	
	Reduction by 50% for filing by small entity (Note 37 C.F.R. §§ 1.9, 1.27 & 1.28).					
	* Reissue claims in excess of 20 and over original patent.					
	** Reissue independent claims over original patent.					
	TOTAL =					790.00
6.	Small entity status:					
a.	<input type="checkbox"/> A small entity statement is enclosed, if (b) and (c) do not apply.					
b.	<input type="checkbox"/> A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.					
c.	<input type="checkbox"/> Is no longer claimed.					
7.	The Commissioner is hereby authorized to credit overpayments or charge the following fees to					
	Deposit Account No. 23 - 0830					
a.	<input type="checkbox"/> Fees required under 37 C.F.R. § 1.16.					
b.	<input type="checkbox"/> Fees required under 37 C.F.R. § 1.17.					
c.	<input type="checkbox"/> Fees required under 37 C.F.R. § 1.18.					
8.	<input checked="" type="checkbox"/> A check in the amount of \$ 790.00 is enclosed.					
9.	<input type="checkbox"/> Other:					

NOTE:

*The prior application's correspondence address will carry over to this CPA
UNLESS a new correspondence address is provided below.*

10. NEW CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number or Bar Code Label			or <input type="checkbox"/> New correspondence address below		
(Insert Customer No. or Attach bar code label here)					
Name	Jeffrey D. Moy				
	HARRY M. WEISS & ASSOCIATES, P.C.				
Address	4204 North Brown Avenue				
City	Scottsdale	State	Arizona	Zip Code	85251-3914
Country	USA	Telephone	(602) 994-8888	Fax	(602) 947-2663

11. SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

Name (Print/Type)	Jeffrey D. Moy
Signature	
Registration No. (Attorney/Agent)	39,307
Date	



CERTIFICATE OF MAILING via EXPRESS MAIL
37 C.F.R. § 1.10

RECEIVED

AUG 21 2001

TECHNOLOGY CENTER 2800

PURSUANT TO 37 C.F.R. § 1.10, I HEREBY CERTIFY THAT I HAVE A REASONABLE BASIS FOR BELIEF THAT THIS CORRESPONDENCE IS BEING DEPOSITED WITH THE UNITED STATES POSTAL SERVICE AS EXPRESS MAIL POST OFFICE TO ADDRESSEE, IN AN ENVELOPE ADDRESSED TO:

HONORABLE COMMISSIONER OF PATENTS

WASHINGTON, D.C., 20231

ON AUGUST 15, 2001.

RONALD L. CHICHESTER (REG. NO. 36,765)

AUGUST 15, 2001

DATE

EL905241833US
EXPRESS MAIL LABEL

APPLICATION NUMBER:	09/522,026
FILING DATE:	OCTOBER 8, 1998
FIRST NAMED INVENTOR:	FINK, ET AL.
GROUP ART UNIT:	2508
EXAMINER:	UNASSIGNED
ATTORNEY DOCKET NUMBER:	068354.0161

INCLUDED IN THIS MAILING FOR THE ABOVE-REFERENCED PATENT APPLICATION ARE:

1. CHANGE OF CORRESPONDENCE ADDRESS FOR APPLICATION (PTO/SB/122);
2. POWER OF ATTORNEY;
3. RETURN POSTCARD TO ACKNOWLEDGE RECEIPT OF ABOVE ITEMS.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Scott Fink et al

Serial No.: 09/522,026

Filed: October 8, 1998

For: A Microcontroller Having an N-Bit Data
Bus Width with Less than N I/O Pins
and Method Therefor



§
§
§ Group Art Unit: 2508
§
§ Examiner: R. Potter
§
§
§
§
§ Atty Docket: M71462USD1

Office of the Deputy Assistant
Commissioner for Patent Policy and Projects
Washington, D.C. 20231

Dear Sir:

EXPRESS MAIL MAILING LABEL NUMBER: EL487680530US DATE OF DEPOSIT: July 24, 2000
I hereby certify that this paper or fee is being deposited with the United States Postal Service "EXPRESS MAIL POST OFFICE TO ADDRESSEE" service under 37 CFR 1.10 on the date indicated below and is addressed to: Office of the Deputy Assistant Commissioner for Patent Policy and Projects Washington, D.C. 20231, on the date below:
July 24, 2000 <i>Kerry Thomas</i> _____ Signature

PRELIMINARY AMENDMENT

Applicants hereby submit a Preliminary Amendment for the above-identified patent application. Applicants respectfully request that the amendments set forth below be entered before prosecution on the merits.

AMENDMENT

In the Claims:

Please cancel claims 1-10 and add the following new claims:

-- 11. A method of operating a microcontroller in an integrated circuit package (IC),
said method comprising the steps of:

providing an IC chip with a microcontroller having a data bus;

providing a first pin electrically coupled to said microcontroller, wherein said first pin functions as a power supply pin;

providing a second pin electrically coupled to said microcontroller, wherein said second pin functions as a grounding pin; and

providing a plurality of third pins electrically coupled to said microcontroller, wherein said plurality of third pins are function pins, at least one of said plurality of third pins being a multiple function pin, whereby a total number of said first, second and plurality of third pins is at least three which is less than or equal to a bit bus width of said data bus.

12. The method of claim 11, wherein each of said plurality of third pins are one of input only pins or input/output pins.

13. The method of claim 11, further comprising the step of providing at least one configuration circuit coupled to each of said plurality of third pins and to said data bus for determining a function for a corresponding one of said plurality of third pins.

14. The method of claim 13, wherein the step of determining a function for a corresponding one of said plurality of third pins comprises the step of enabling only one at a time of said at least one configuration circuits for each of said plurality of third pins so as to configure a corresponding one of said plurality of third pins to a function associated with said enabled one of said at least one configuration circuits.

15. The method of claim 13, further comprising the step of coupling independent function lines to each of said configuration circuits and to a corresponding one of said plurality

of third pins for transferring data between said corresponding one of said plurality of third pins and said microcontroller when a particular one of said configuration circuits is enabled.

16. The method of claim 15, further comprising the step of coupling a signal bus to said control register and to said microcontroller for sending signals from said microcontroller to said control register on which of said configuration circuits need to be enabled and which of said configuration circuits need to be disabled.

17. The method of claim 13, further comprising the step of coupling a control register to said data bus for enabling and disabling each of said configuration circuits for determining a function for each of said plurality of third pins.

18. The method of claim 17, further comprising the step of coupling control signal lines to said data bus and to each of said configuration circuits for transferring to each of said configuration circuits one of said enable and disable signals.

19. The method of claim 17, wherein said control register is adapted to hold a known logic state.

20. The method of claim 17, wherein said control register is a memory device.

21. A method of operating a microcontroller in an integrated circuit package (IC), said method comprising the steps of:

providing an IC chip with a microcontroller having a data bus;
providing a first pin electrically coupled to said microcontroller, wherein said first pin functions as a power supply pin;

providing a second pin electrically coupled to said microcontroller, wherein said second pin functions as a grounding pin;

providing a plurality of third pins electrically coupled to said microcontroller, wherein said plurality of third pins are function pins, at least one of said plurality of third pins being a multiple function pin, whereby a total number of said first, second and plurality of third pins is at least three which is less than or equal to a bit bus width of said data bus;

providing at least one configuration circuit coupled to each of said plurality of third pins and to said data bus for determining a function for a corresponding one of said plurality of third pins, wherein only one of said at least one configuration circuit for each of said plurality of third pins is enabled at a time to configure a corresponding one of said plurality of third pins to a function associated with said one of said at least one configuration circuit which is enabled;

coupling independent function lines to each of said configuration circuits and to a corresponding one of said plurality of third pins for transferring data between said corresponding one of said plurality of third pins and said microcontroller when a particular one of said configuration circuits is enabled;

coupling a control register to said data bus for enabling and disabling each of said configuration circuits for determining a function for each of said plurality of third pins;

coupling control signal lines to said data bus and to each of said configuration circuits for transferring to each of said configuration circuits one of said enable and disable signals; and

coupling a signal bus to said control register and to said microcontroller for sending signals from said microcontroller to said control register on which of said configuration circuits need to be enabled and which of said configure circuits need to be disabled.

22. The method of claim 21, wherein each of said plurality of third pins are one of input only pins or input/output pins.

23. The method of claim 21, wherein said control register is adapted to hold a known logic state.

24. The method of claim 21, wherein said control register is a memory device.--

Applicants respectfully request that the amendments below be entered and submit that these amendments will put the claims in condition for allowance, or in better form for appeal. No new matter has been entered. Antecedent basis for the amendments may be found throughout the specification and drawings as originally filed.

Applicants request reconsideration in light of the amendments and remarks contained herein.

Respectfully submitted,

DATE: July 24, 2000

BY: Paul N. Katz

Paul N. Katz

Registration No. 35,917

Frohwitter

Three Riverway, Suite 500

Houston, Texas 77056

Phone: (713) 621-0703

Fax: (713) 622-1624

ATTORNEY FOR APPLICANTS



PATENT

**A MICROCONTROLLER HAVING AN N-BIT DATA BUS WIDTH
WITH LESS THAN N I/O PINS AND A METHOD THEREFOR**

RECEIVED

OCT 14 1998

GROUP 2100

RELATED APPLICATIONS

5

This application is a Divisional Application of U.S. patent application Serial Number 08/644,916, filed May 24, 1996, in the name of the same inventors as the present patent application.

BACKGROUND OF THE INVENTION

10

1. Field of the Invention

This invention is in the field of microcontrollers and methods therefor and, more particularly, is a microcontroller having an n-bit architecture (i.e., data bus width) with less than n Input/Output (I/O) pins and a method therefore.

15

2. Description of the Related Art

20

Microcontrollers are widely known and used in many different applications. A typical architecture used in microcontrollers today is the 8-bit architecture (i.e., the data bus width of the microcontroller is 8 bits wide). One problem with this and other sizes of microcontrollers is that to support an n-bit architecture, greater than n pins are required to be connected to the microcontroller. By reducing the number of pins required to support an n-bit, or more

particularly, an 8-bit microcontroller, the overall cost of using the device is reduced, and limited space is conserved. Therefore, there existed a need to provide a microcontroller having an n-bit architecture with less than or equal to n pins and a method therefor.

25

SUMMARY OF THE INVENTION

An object of the present invention is to provide a microcontroller having an n-bit architecture with less than or equal to n pins coupled to the microcontroller and a method therefor.

30

Another object of the present invention is to provide a microcontroller having an n bit architecture with the number of I/O pins less than n and a method therefor.

Yet another object of the present invention is to provide a microcontroller package with pins for performing multiple functions and a method therefor.

Still another object of the present invention is to provide a microcontroller with n-bit data processing capability and fewer than n I/O pins and a method therefor.

35

BRIEF DESCRIPTION OF THE PREFERRED EMBODIMENTS

According to the present invention, an Integrated Circuit (IC) package is disclosed comprising, in combination, an IC chip with a microcontroller therein having an n-bit data bus, and up to n pins electrically coupled to the microcontroller. The IC package further comprises 40 control register means coupled to the microcontroller for receiving enable and disable signals.

45

50

55

Pin function configuration means are also included coupled to the control register means for determining a function for a corresponding one of the n pins. The pin function configuration means comprises at least one functional block means coupled to the control register means for determining a function for a corresponding pin. The pin function configuration means may comprise a plurality of the functional block means each coupled to the control register means and to a corresponding pin of the n pins for determining a different function for the corresponding one of the n pins. The control register means provides independent control line means to each functional block means for transferring to each function block means one of the enable and the disable signals. Only one of the functional block means per pin is enabled at a time by the enable signal to configure a corresponding pin for a function associated with the enabled functional block means. Each functional block means is coupled to a corresponding one of the n pins and to the microcontroller for transferring data between the corresponding pin and the microcontroller when a particular one of the functional blocks is enabled. Additionally, the n pins include a number of Input/Output (I/O) type pins less than n.

Alternatively, a method of operating an Integrated Circuit (IC) package is disclosed comprising the steps of providing an IC chip with a microcontroller therein having an n-bit data bus, and providing up to n pins electrically coupled to the microcontroller.

60

The foregoing and other objects, features, and advantages of the invention will be apparent from the following, more particular, description of the preferred embodiments of the invention, as illustrated in the accompanying drawing.

BRIEF DESCRIPTION OF THE DRAWING

Fig. 1 is a simplified block diagram view of the IC microcontroller package having an n-bit data bus and n pins.

65

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figure 1, the IC package or package of the instant invention is shown and generally designated by reference number 10. IC package 10 comprises an IC chip 11 with a microcontroller core or simply microcontroller 12 therein having an n-bit Data Bus (DB), and up to n pins 34-38 electrically coupled to the microcontroller 12. The manner of fabricating IC packages 10, chips 11, and microcontrollers 12 are well known to those skilled in the art. Microcontroller 12 has, in general, an n-bit wide data bus, but more specifically here an 8-bit architecture or data bus width. Note that the data bus itself is not shown in detail for simplification of the drawing.

The IC package 10 further comprises a control register 16 coupled to the microcontroller 12 via a control signal bus 14 for receiving enable and disable signals from the microcontroller 12. Control registers are well known to those skilled in the art. The control register 16 can be any element that can hold a known state (i.e., charge, current, or voltage) such as SRAM, DRAM, EPROM, EEPROM, ROM, Combinational Logic, PROM, or the like. The control register 16 provides sufficient memory capacity to store and transfer the enable and disable signals sent from the microcontroller 12 to the functional blocks 26, which will be described

later. The communications protocol for sending the enable and disable signals from the microcontroller 12 to the functional blocks 26 via the control register 16 is well known to those skilled in the art. The enable and disable signals are routed from the control register 16 to the appropriate functional blocks 26 via buses 18-24. From buses 22 and 24, each functional block 26 is coupled via connector 28 to receive the enable or disable signal sent from the control register 16. Note also that each functional block 26 has a connection 32 to a respective pin 34 to transfer data to or from the pin 34. Additionally, each functional block 26 has a connection 30 to the microcontroller 12 to transfer to or receive from the microcontroller 12 the appropriate data.

Note that pins 36 and 38 have no functional blocks 26 coupled thereto. This is because these pins 36 and 38 are the power and ground supply pins for the package 10, and therefore, they require no functional blocks 26. Note that the individual power and ground lines from pins 36 and 38 are not shown for simplification of the drawing. Pins 34 represent either input only or I/O type pins, both of which are well known in the art. Which of pins 34 are input only and which are I/O type depends on the user's application. Note that the second pin 34 from the top left corner of the package 10 only has one functional block 26 coupled to it. Thus, this particular pin 34 has only one function associated with it. Note that this single function depiction is shown only for the purpose of demonstrating how a single function pin 34 would look. Thus, any of the pins 34 could be single function pins, or multiple function pins 34. Additionally, note that the other pins 34 are shown with two functional blocks 26 per pin 34, and therefor these pins 34

have two functions. In other words, the number of functions per pin 34 equals the number of functional blocks associated with that pin 34. Accordingly, any of the pins 34 could have one, two, or more functional blocks 26 associated thereto. This is represented in the drawing by the dashed lines between the functional blocks 26. Additionally note the dashed lines between pins 105 34, which indicate that this package 10 could have more or less than eight pins 34-38, but the key is that the number of pins 34-38 is less than or equal to the data bus width of the microcontroller 12.

110 The pin function configuration portion of the package 10 is defined as simply one or more functional blocks 26. The internals of the functional blocks 26 are not shown for simplification of the drawing. The functions that pins 34-38 must support for a microcontroller 12 are well known to those skilled in the art such as a Bi-Directional I/O Port pin, a Serial Programming Data pin, a Serial Programming Clock pin, and the like. The point is that there are many functions that pins 34-38 support for a microcontroller 12, they are all well known, and need not be specifically designated. Further, functional blocks 26, which enable a particular pin 34-38 to 115 behave as required for a given function, are also well known in the art, and therefore need not be shown in detail. A key feature of the instant invention is that because pins 34 are multi-functional, only n pins 34-38 are required and all data control commands for the microcontroller 12 having an n-bit (i.e., 8-bit) data bus use the full n-bit bus.

OPERATION

Referring to Figure 1, when executing an instruction, the microcontroller 12 sends appropriate control signals to the control register 16, which enables and disables the appropriate functional blocks 26 for a given pin 34. Note that since several functional blocks 26 can be used per pin 34, only one functional block can be enabled at a time. Data travels into the package 10 from a pin 34, through a corresponding connector 32, the enabled functional block 26, a corresponding connector 30, and to the microcontroller 12. The reverse path sends data from the microcontroller 12 out of a particular pin 34 of the package 10. Whether the flowpath of data be into or out of the microcontroller 12, the microcontroller 12 sends appropriate enable and disable signals to the appropriate functional blocks 26 in order to operate the desired pins 34 as required.

Although the invention has been particularly shown and described with reference to a preferred embodiment thereof, it will be understood by those skilled in the art that changes in form and detail may be made therein without departing from the spirit and scope of the invention.

135

What is Claimed is:

1. A method of operating an Integrated Circuit (IC) package comprising the steps

of:

providing an IC chip with a microcontroller therein having an n-bit data bus; and

providing up to n pins electrically coupled to said microcontroller.

140

2. The method Claim 1 further comprising the step of providing control register means coupled to said microcontroller for receiving enable and disable signals.

145

3. The method Claim 2 further comprising the step of providing pin function configuration means coupled to said control register means for determining a function for a corresponding one of said n pins.

4. The method of Claim 3 wherein the step of providing said pin function configuration means comprises the step of providing at least one functional block means coupled to said control register means for determining a function for a corresponding pin.

150

5. The method of Claim 4 wherein the step of providing said pin function configuration means comprises the step of providing a plurality of said functional block means each coupled to said control register means and to a corresponding pin of said n pins for determining a different function for said corresponding one of said n pins.

155

6. The method of Claim 4 wherein the step of providing said control register means provides independent control line means to each functional block means for transferring to each function block means one of said enable and said disable signals.

160

7. The method of Claim 6 wherein only one of said functional block means per pin is enabled at a time by said enable signal to configure a corresponding pin for a function associated with said enabled functional block means.

165 8. The method of Claim 6 wherein each of said functional block means is coupled to a corresponding one of said n pins and to said microcontroller for transferring data between said corresponding pin and said microcontroller when a particular one of said functional blocks is enabled.

170 9. The method of Claim 1 wherein the step of providing up to said n pins includes the step of providing a number of Input/Output (I/O) type pins less than n .

10. The IC package of Claim 1 wherein data control commands of said microcontroller operate upon n -data bits.

U.S.S.N.: 09/522,026
Filed: October 8, 1998
Applicant: Fink, et al.




FIG. 1



DECLARATION

SOLE/JOINT INVENTOR
ORIGINAL/SUBSTITUTE/CIP

As a below named inventor, I hereby declare that my residence, post office address, and citizenship are as stated below next to my name. I believe I am the original, first, and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

A MICROCONTROLLER HAVING AN N-BIT DATA BUS WIDTH WITH LESS THAN N I/O PINS AND A METHOD THEREFOR

as described in the specification attached or of Patent Application Serial No. 09/522,026 filed 10/08/98.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above; that I do not know and do not believe the same was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application; that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representative or assigns more than twelve months prior to this application; and that I acknowledge the duty to disclose information of which I am aware which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations § 1.56(a). Such information is material when it is not cumulative to information already of record or being made of record in the application, and

- (1) it establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim; or
- (2) it refutes, or is inconsistent with, a position the applicant has taken or may take in:
 - (i) opposing an argument of unpatentability relied on by the Office, or
 - (ii) asserting an argument of patentability.

I hereby claim foreign priority benefits under Title 35, United States Code § 119 of any foreign application(s) for patent or inventor's certificates listed below and have also identified below any foreign application(s) having a filing date before that of the application(s) on which priority is claimed:

COUNTRY	APPLICATION NUMBER	DATE OF FILING	PRIORITY CLAIMED UNDER 35 USC 119
			<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

I hereby claim the benefit under Title 35 United States Code § 120 of any United States application(s) listed below and, insofar as any subject matter of any claim of this application is not disclosed in the prior United States Application, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Serial No. 08/644,916 filed May 24, 1996 – Patent No. 5,847,450

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF FIRST JOINT INVENTOR Scott Fink	INVENTOR'S SIGNATURE 	DATE 7/18/00
RESIDENCE 6327 Yucca, Glendale, AZ 85304		CITIZENSHIP U.S.A.
POST OFFICE ADDRESS 6327 Yucca, Glendale, AZ 85304		
FULL NAME OF SECOND JOINT INVENTOR Gregory Bingham	INVENTOR'S SIGNATURE 	DATE 7/24/00
RESIDENCE 440 Bay Shore Blvd., Gilbert, AZ 85233		CITIZENSHIP U.S.A.
POST OFFICE ADDRESS 440 Bay Shore Blvd., Gilbert, AZ 85233		

JUL-24-2000 10:21

MICROCHIP LEGAL

480 917 4112 P.03/03

FULL NAME OF THIRD JOINT INVENTOR
Richard Hull

INVENTOR'S SIGNATURE

Richard I. Hull

DATE

7/21/00

CITIZENSHIP

U.S.A.

RESIDENCE

2138 W. Monroe Street, Chandler, AZ 85244

POST OFFICE ADDRESS

2138 W. Monroe Street, Chandler, AZ 85244

FULL NAME OF FOURTH JOINT INVENTOR

Scott Ellison

INVENTOR'S SIGNATURE

Scott Ellison

DATE

7/18/00

CITIZENSHIP

U.S.A.

RESIDENCE

250 South Elizabeth Way, #2121, Chandler, AZ 85225

POST OFFICE ADDRESS

250 South Elizabeth Way, #2121, Chandler, AZ 85225

TOTAL P.03

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE


Applicant/Patentee: Scott Fink

Filed: 10/08/98

Serial No.: 09/522,026

For: MICROCONTROLLER HAVING AN N-BIT
DATA BUS WIDTH LESS THAN N I/O PINS
AND A METHOD THEREFOR

Atty File: M71462USD1



POWER OF ATTORNEY BY ASSIGNEE

Under the provisions of 37 C.F.R. § 3.71, the undersigned assignee of record of the entire interest in the above-identified patent/patent application by virtue of an assignment elects to conduct the prosecution of the application/maintenance of the patent to the exclusion of the inventor(s). The undersigned hereby declares that he has reviewed the above-referenced assignment and hereby declares that, to the best of his knowledge, title is in the Assignee, and further declares that all statements made herein of his own knowledge are true and that all statements made on information and belief are believed to be true. The assignee hereby revokes any previous powers of attorney and appoints the following to prosecute this application/maintain this patent and transact all business in the Patent and Trademark Office connected therewith:

Ronald L. Chichester	36,765	R. William Beard, Jr.	39,903
Paul N. Katz	35,917	Paul R. Morico	35,960
Bruce W. Slayden, II	33,790	Catherine L. Bell	35,444
Ari O. Pramudjji	45,022	Christopher J. Buntel	44,573

Please direct all communications to: Frohwitter, Three Riverway, Suite 500, Houston, Texas 77056 (713) 621-0703, Fax (713) 622-1624, to the attention of: Paul N. Katz.

ASSIGNEE
MICROCHIP TECHNOLOGY INC.

Date: June 20, 2000

BY.

Mark Johnson

NAME: Mary K. Simmons
TITLE: Vice President, General Counsel
and Secretary

08-16-01

2508
2806Please type a plus sign (+) inside this box → Approved for use through 10/31/2002. OMB 0651-0035
U.S. Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.



RECEIVED

SEARCHED

**CHANGE OF
CORRESPONDENCE ADDRESS**
Application
Address to:
 Assistant Commissioner for Patents
 Washington, D.C. 20231

Application Number	09/522,026
Filing Date	October 8, 1998
First Named Inventor	Scott FINK, et al.
Group Art Unit	2508
Examiner Name	
Attorney Docket Number	068354.0161

Please change the Correspondence Address for the above-identified application to:

 Customer Number

023640

Type Customer Number here

 Place Customer
Number Bar Code
Label here

OR

<input checked="" type="checkbox"/> Firm or Individual Name	Ronald L. Chichester			
Address	Baker Botts L.L.P.			
Address	910 Louisiana Street			
City	Houston,	State	TX	ZIP 77002-4995
Country	USA			
Telephone	713.229.1341	Fax	713.229.7741	

This form cannot be used to change the data associated with a Customer Number. To change the data associated with an existing Customer Number use "Request for Customer Number Data Change" (PTO/SB/124).

I am the :

- Applicant/Inventor.
- Assignee of record of the entire interest.
- Statement under 37 CFR 3.73(b) is enclosed. (Form PTO/SB/96).
- Attorney or Agent of record.
- Registered practitioner named in the application transmittal letter in an application without an executed oath or declaration. See 37 CFR 1.33(a)(1). Registration Number _____

Typed or Printed Name

Ronald L. Chichester

Reg. No. 36,765

Signature

Date


August 15, 2001

NOTE: Signatures of all the inventors or assignees of record of the entire interest or their representative(s) are required. Submit multiple forms if more than one signature is required, see below*.

 *Total of _____ forms are submitted.

Burden Hour Statement: This form is estimated to take 3 minutes to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

 Express Mail:
 EL905241833US



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE *RECEIVED*

Applicant/Patentee:

FINK, et al.

Group Art Unit:

2508

AUG 21 2001

TECHNOLOGY CENTER 2800

Serial No.: **09/522,026**

Examiner: *To be Assigned*

Filed: **OCTOBER 8, 1998**

Atty File: **068354.0161**

Title: **"A MICROCONTROLLER HAVING AN N-BIT
DATA BUS WIDTH WITH LESS THAN N I/O
PINS AND METHOD THEREFOR"**

POWER OF ATTORNEY BY ASSIGNEE

Under the provisions of 37 C.F.R. § 3.71, the undersigned assignee of record of the entire interest in the above-identified patent/patent application by virtue of an assignment recorded (check as applicable):

Concurrently Herewith

Date Recorded:

Reel/Frame:

elects to conduct the prosecution of the application/maintenance of the patent to the exclusion of the inventor(s). The undersigned hereby declares that he has reviewed the above-referenced assignment and hereby declares that, to the best of his knowledge, title is in the Assignee, and further declares that all statements made herein of his own knowledge are true and that all statements made on information and belief are believed to be true. The assignee hereby revokes any previous powers of attorney and appoints the following to prosecute this application/maintain this patent and transact all business in the Patent and Trademark Office connected therewith:

R. William Beard, Jr.: 39,903	Ronald L. Chichester: 36,765	Claude E. Cooke, Jr.: 34,142	Roger J. Fulghum: 39,678
Michael A. Hawes: 38,487	Carey J. Hetherington: 47,646	Paul N. Katz: 35,917	Michael G. Locklar: 44,878
Mitchell D. Lukin: 30,772	Jerry W. Mills: 23,005	Paul R. Morico: 35,960	Robert Neuner: 24,316
Scott F. Partridge: 28,142	Bruce W. Slayden, II: 33,790	Howard L. Speight: 37,733	Lori D. Stiffler: 36,939
Khannan Suntharam: 45,144	Melissa J. Szanto: 40,834	G. Alan Witte: 36,061	Joseph Uradnik: 36,955

Please direct all communications to: **Baker Botts L.L.P., One Shell Plaza, 910 Louisiana Street, Houston, Texas 77002-4995, 713.229.1343, Fax: 713.229.7743, attention of: Paul N. Katz.**

ASSIGNEE
MICROCHIP TECHNOLOGY INC.

DATE: August 10, 2001

BY: Mary K. Simmons

NAME: Mary K. Simmons

TITLE: Vice President & General Counsel